

TECHNICAL INFORMATION:**Physical Properties**

Mixing Ratio, by Weight	8 oz. per 1.5 gallons of resin
Solids Content	100%
V.O.C.	None

LIMITATIONS:

- Exterior applications must be made with a UV-stable binder.

WARRANTY:

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for damages caused by application of its products over concrete with excessive moisture vapor transmission or alkalinity. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 201 Arizona Polymer Flooring, Inc

8 8BUOT 4U 1IPFO

.435.2277 Tel. / 23.435.8585 Fax

www.super-krete.com

ColorChrome Pigment

032317

