SAFETY DATA SHEET

Issuing Date 10-Nov-2015 Revision Date 10-Nov-2015 Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name S-1800 Super-Stamp Gray

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Industrial Use Only

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Arizona Polymer Flooring, Inc.

Supplier Address 2705 Via Orange Way Suite B

Spring Valley

CA 91978 US

Supplier Phone Number Phone:619-401-8282

Fax:619-401-8288

Supplier Website www.super-krete.com

Emergency telephone number

Company Emergency Phone

800-424-9300

Number

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Carcinogen	Category 1A
Specific Target Organ Toxicity (STOT) following repeated exposures	Category 1
Eye Damage/Eye Irritation	Category 1
Skin Irritant	Category 2

GHS Label elements, including precautionary statements: Carcinogen

Emergency Overview

Signal word

Warning

Hazard Statements

May cause cancer by inhalation.

Causes damage to lungs, kidneys and autoimmune system through prolonged or repeated exposure by inhalation.

Causes skin irritation and serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.





Appearance Gray

Physical state Solid/Powder Solid

Odor None

Precautionary Statements – Prevention

Do not handle until the safety information presented in this SDS has been read and understood.

Do not eat, drink or smoke while manually handling this product.

Wash face, hands and any exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Avoid creating dust when handling, using or storing.

Use with adequate ventilation to keep exposure below recommended

exposure limits.

Contaminated work clothing should not be allowed out of the workplace.

Use only outdoors or in a well-ventilated area.

Wear eye and respiratory protection following this SDS, NIOSH guidelines and other applicable regulations.

Precautionary Statements - Response

Specific treatment (see supplemental first aid instructions on this label)

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

IF ON SKIN: Rinse skin after manually handling and wash contaminated clothing if there is potential for direct skin contact before reuse. Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention

Ingestion

IF SWALLOWED: Rinse mouth and do not induce vomiting.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell

If exposed, concerned, unwell or irritation of the eyes, skin, mouth or throat/nasal passage persist: Get medical attention.

Page 2/12

Precautionary Statements - Storage

Keep stored off the ground and away from walls in a cool, dry, well ventilated area. Do not allow exposure to moisture or water. Store in a tightly closed container.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant. Dispose of the product in accordance with local, regional, national or international regulations.

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

100% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Supplier Trade Secret	Proprietary	30 - 60	*
Supplier Trade Secret	Proprietary	15 - 40	*
Supplier Trade Secret	Proprietary	10 - 30	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

Revision Date 10-Nov-2015

4. FIRST AID MEASURES

First aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an

allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an

unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Effects

Burning sensation. Itching. Rashes. Hives. Coughing and/ or wheezing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician May cause sensitization of susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Product is or contains a sensitizer. May cause sensitization by skin contact.

Uniform Fire Code Sensitizer: Solid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, OSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off

contaminated clothing and wash before reuse. Do not breathe dust.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Avoid freezing

temperatures during storage. Keep out of the reach of children. Do not allow exposure to

moisture or water.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

D. . . 5/40

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Supplier Trade Secret	TWA: 0.025 mg/m ³ respirable	TWA: 0.1 mg/m³ (vacated)	IDLH: 50 mg/m3 respirable dust
	fraction		TWA: 0.05 mg/m³ respirable dust
Supplier Trade Secret	TWA: 1 mg/m³ particulate matter		IDLH: 5000 mg/m ³
	containing no asbestos and <1%	TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m ³ total dust
	crystalline silica, respirable	(vacated) TWA: 10 mg/m³ total	TWA: 5 mg/m ³ respirable dust
	fraction	dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
		TWA: 50 mppcf <1% Crystalline	
		silica	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Engineering Controls Ventilation: Use local exhaust, general ventilation or natural ventilation adequate to maintain

exposures below appropriate exposure limits.

Other control measures Respirable dust and crystalline silica levels should be monitored regularly. Dust levels in

excess of appropriate exposure limits should be reduced by implementing feasible engineering controls, including (but not limited to) dust suppression (wetting), ventilation,

process enclosure and enclosed employee work stations.

Eye/Face Protection Safety glasses with side shields should be worn as minimum protection. Dust goggles should

be worn when excessively (visible) dusty conditions are present or are anticipated. If irritation persists, get medical attention immediately. There is potential for severe eye irritation if

exposed to excessive concentrations of dust for those using contact lenses.

Skin Protection Chemical resistant apron. Loose clothing, with the neck closed and sleeves rolled down.

Safety shoes should be laced so that no openings are left through which concrete may reach the skin. Use appropriate chemical resistant protective gloves if manually handling the

product.

General Hygiene Considerations

There are no known hazards associated with this material when used as recommended. Following the guidelines in this SDS are recognized as good industrial hygiene practices. Avoid breathing dust. Avoid skin and eye contact. Wash dust-exposed skin with soap and water before

eating, drinking, smoking and using toilet facilities. Wash work clothes after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Solid/Powder, Solid

Appearance Gray Odor None

Color No information available Odor Threshold No information available

Property Values Remarks Method

pH No data available None known

Melting / freezing point No data available None known

Boiling point / boiling range No data available None known

Flash Point No data available None known

Evaporation RateNo data availableNone knownFlammability (solid, gas)No data availableNone known

Flammability Limit in Air

Upper flammability limit No data available

Lower flammability limit No data available

Vapor pressure No data available None known

Vapor density No data available None known **Specific Gravity** No data available None known **Water Solubility** Slightly soluble None known No data available Solubility in other solvents None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known No data available **Decomposition temperature** None known Kinematic viscosity No data available None known

Dynamic viscosity No data available None known

Explosive propertiesNo data availableOxidizing propertiesNo data available

Other Information

Softening Point

VOC Content (%)

Particle Size

No data available
No data available
No data available

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Page 7/12

Conditions to avoid

None known based on information supplied.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

<u>Health Effects:</u> The information below represents an overview of health effects caused by overexposure to one or more components in Portland cement.

Primary routes of exposure:

Eye Contact: Direct contact with dust may cause irritation by mechanical abrasion or corrosive

action. Conjunctivitis may occur.

Skin Contact: Direct contact may cause irritation by mechanical abrasion. Some components of material are

also known to cause corrosive effects to skin and mucous membranes.

Skin Absorption: Not expected to be a significant route of exposure.

Ingestion Small amounts (a tablespoonful) swallowed during normal handling operations are not

likely to cause injury. Ingestion of large amounts may cause gastrointestinal irritation

and blockage.

Inhalation: Dust may irritate nose, throat, mucous membranes and respiratory tract by mechanical

abrasion. Coughing, sneezing, chest pain, shortness of breath, inflammation of mucous membrane, and flu-like fever may occur following exposures in excess of appropriate

exposure limits.

Medical Conditions Aggravated

by Exposure:

Inhaling respirable dust may aggravate existing respiratory system disease(s) (e.g., bronchitis, emphysema, chronic obstructive pulmonary disease) and/or dysfunctions. Exposure to dust may aggravate existing skin and/or eye conditions. Smoking and obstructive/restrictive lung diseases may also exacerbate the effects of excessive exposure to this product. This product is a mixture of components including Portland

Cement.

Portland Cement:

Exposure Routes: Inhalation, ingestion, skin and/or eye contact

Target Organs: Eyes, skin, respiratory system.

Acute Effect: Exposure to dry portland cement may cause drying of the skin and mild irritation, or

more significant effects from the aggravation of other conditions. Eye exposures to portland cement may cause immediate or delayed irritation or inflammation of the cornea. Eye contact with larger amounts of dry powder or splashes of liquid portland cement may cause effects ranging from moderate eye irritation to chemical burns and blindness. Inhalation of dry portland cement may cause irritation to the moist mucous

membranes of the nose, throat and upper respiratory system, or may cause or

aggravate certain lung diseases or conditions.

D---- 0.140

Chronic Effect: Prolonged exposure can cause severe skin damage in the form of chemical (caustic)

burns. Portland Cement is not listed as carcinogen on the NTP, IARC or OSHA list of carcinogens, however Portland Cement contains trace amounts of hexavalent chromium [Cr(VI)] and certain chromium compounds which are listed on the NTP and IARC lists of carcinogens. The total amounts of chromium and chromium compounds in Portland Cement are typically less than 0.003% and hexavalent chromium less than 0.001%. Note: Some individuals who are exposed to portland cement may exhibit an allergic response, which can result in symptoms ranging from mild rashes to severe skin ulcers. Cement dermatitis may be irritant contact dermatitis induced by the alkaline or it may be allergic contact dermatitis elicited by an immunological reaction to Cr(VI),

or it may be a combination of the two.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Supplier Trade Secret			Known	X

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

CALIFORNIA PROPOSITION 65 Crystalline silica in October 1996 was listed on the Safe Drinking Water and Toxic

Enforcement ACT of 1986 as a chemical known to the state to cause cancer or reproductive

toxicity.

Reproductive toxicity No information available.

STOT - single exposure Respiratory system.

STOT - repeated exposure Specific Target Organ Toxicity.

Chronic Toxicity No known effect based on information supplied. Contains a known or suspected

carcinogen.

Target Organ Effects Respiratory system. Eyes. Skin.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Not applicable

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methodsThis material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT NOT REGULATED

Proper Shipping Name NON REGULATED

Hazard Class N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

<u>IATA</u> Not regulated

Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard .	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Silica Sand	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Silica Sand	X	X	X	X	
Portland Cement	X	X	X		

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Respirable Crystalline		Mexico: TWA= 0.1 mg/m ³
Silica (15 - 40)		_

Portland Cement	Mexico: TWA 10 mg/m ³
(10 - 30)	Mexico: STEL 20 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Not determined

16. OTHER INFORMATION

NFPA Health Hazards 2 Flammability 0 Instability 0 Physical and Chemical Hazards - HMIS Health Hazards 2 Flammability 0 Physical Hazard 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501 10-Nov-2015

Revision Date Revision Note

User's Responsibility

The OSHA Hazard Communication Standard 29 CFR 1910.1200 requires that this SDS be made available to your employees who handle or may be exposed to this product. Educate and train your employees regarding applicable precautions. Instruct your

employees to handle this product properly.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet