

LIMITATIONS:

- Use over dense, minimally profiled surfaces requires machine scrubbing with a nylogrit type brush.
- Do not use solvent acrylic as a primer for SK-P250 VOC.
- Applications heavier than 200 sq. ft. per gallon or puddling may result in solvent entrapment and possible blistering.
- Do not use the satin material over an unprimed surface.

WARRANTY:

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for damages caused by application of its products over concrete with excessive moisture vapor transmission or alkalinity. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.

Super-Krete[®] Products is a Division of Arizona Polymer Flooring, Inc.

© 201 Arizona Polymer Flooring, Inc

8 8BU0T 4U 1PFOY "

Tel. /

Fax

www.super-krete.com

4,170\$

