



COLORCHROME™

Metallic Epoxy

ColorChrome™ Pigment is a metallic mica pigment that can be dispersed in a variety of binders to create seamless floors with a unique, three-dimensional appearance. Depending on the application techniques used, the finished floor's appearance can range from elegant to exotic. ColorChrome Pigment is ideal for retail establishments, night clubs, automotive showrooms, residential interiors, garage floors or any installation requiring a truly unique finished floor. When combined with the proper binders and finish coats, it can offer an unmatched blend of beauty and durability.

Espresso




Copper



Golden Brown



Ash Brown



Autumn



Verde



Satin Bronze



Burnt Umber



Canary



Iridescent Blue




Citrine



Crimson



Coral**Pearl****Ruby****Gun Metal****Graphite****Mercury****Cambridge Blue****Coffee**

AVAILABLE SYSTEMS

ColorChrome™ Metallic Epoxy System

This designer flooring system possesses a truly unique, three-dimensional appearance that can vary from soft and subtle to striking and vivid. The use of high-performance epoxy/polyurethane resins makes the ColorChrome Metallic Epoxy System an exceptionally durable and long-lasting flooring system.

ColorChrome™ FC Metallic Epoxy System

This fast-curing flooring system possesses a truly unique, three-dimensional appearance that can vary from soft and subtle to striking and vivid, similar to the ColorChrome Metallic Epoxy System yet with added UV stability. The use of high-performance polyaspartic/polyurea resins makes ColorChrome FC Metallic Epoxy System an exceptionally durable and long-lasting flooring system for both interior and exterior applications.

COMMON APPLICATIONS

- Malls & Retail Locations
- Restaurants & Bars
- Casinos & Sports Facilities
- Residential Interiors
- Garage Floors
- Commercial Interiors

*Colors shown are approximate. A sample test is always recommended before beginning any project. The final color of the installed project may vary due to finishing techniques, job conditions and type of sealer used. Physical samples are always recommended to determine actual color and finishes.