

**SAFETY DATA SHEET****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY****MANUFACTURER'S NAME / ADDRESS**

ARIZONA POLYMER FLOORING  
7731 N. 68<sup>TH</sup> AVE.  
GLENDALE, AZ 85303

TRADE NAME: POLYASPARTIC PIGMENT PACK  
COLOR: WHITE AND TINTS  
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

**SECTION 2: HAZARDS IDENTIFICATION****GLOBALLY HARMONIZED SYSTEM (GHS)****CLASSIFICATION:**

SKIN SENSITIZATION: CATEGORY 1

ACUTE TOXICITY, ORAL: CATEGORY 4

CARCINOGENICITY: CATEGORY 2

AQUATIC TOXICITY: CATEGORY 3

**GHS LABEL ELEMENTS****HAZARD PICTOGRAMS**

**SIGNAL WORD:** DANGER!

**HAZARD STATEMENTS**

H332: HARMFUL IF INHALED

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H351: SUSPECTED OF CAUSING CANCER

H402: HARMFUL TO AQUATIC LIFE

**PRECAUTIONARY STATEMENTS:****PREVENTION**

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE

P273: AVOID RELEASE TO ENVIRONMENT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

# SAFETY DATA SHEET

Page 2 of 7

## SECTION 2: HAZARDS IDENTIFICATION CON'T.

### RESPONSE

P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

P303+P361+353: **IF ON SKIN (OR HAIR):** REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING

P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING

P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

P391: COLLECT SPILLAGE

### STORAGE

P403+P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL

P233: KEEP CONTAINER TIGHTLY CLOSED

### DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

**EMERGENCY OVERVIEW:** DANGER!  
HARMFUL IF INHALED  
MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION  
MAY CAUSE SENSITIZATION BY SKIN CONTACT

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>Wt. %</u>	<u>CAS Number</u>
ASPARTIC ESTER	40-70	136210-32-7
TITANIUM DIOXIDE	15-40	013463-67-7
MODIFIED CARBONATE BIS-OXAZOLIDINE	1-5	145899-78-1
IRON (III) OXIDE	0-10	001309-37-1
CARBON BLACK	0-10	001333-86-4

## SECTION 4: FIRST AID MEASURES

**GENERAL:** REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

**EYES:** FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

**SKIN:** REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

**INHALATION:** MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

**INGESTION:** GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

# SAFETY DATA SHEET

Page 3 of 7

## SECTION 5: FIRE FIGHTING MEASURES

**FLASH POINT:** 77°C (171°F) – PMCC

**OSHA CLASS:** IIIB

**CONDITIONS OF FLAMMABILITY:** NA

**AUTO IGNITION TEMP.:** 240°C

**FLAMMABLE LIMITS:** **LEL:** NE **UEL:** NE

**SENSITIVITY TO IMPACT:** NONE

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>, NH<sub>3</sub>, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

**SENSITIVITY TO STATIC DISCHARGE:** NONE

**EXTINGUISHING MEDIA:** IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

**SPECIAL FIRE FIGHTING PROCEDURES:** NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

## SECTION 7: HANDLING AND STORAGE

**HANDLING:** AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

**STORAGE:** KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

## SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
136210-32-7	NE	NE	NE	NE	
013463-67-7	10mg/m <sup>3</sup>	ND	10mg/m <sup>3</sup>	ND	(SEE NOTE 1)
145899-78-1	NE	NE	NE	NE	
001309-37-1	5mg/m <sup>3</sup>	ND	5mg/m <sup>3</sup>	ND	(SEE NOTE 1)
001333-86-4	3.5mg/m <sup>3</sup>	ND	3.5mg/m <sup>3</sup>	ND	(SEE NOTE 1)

**LEGEND:** (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK  
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

**ENGINEERING CONTROLS:** NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

# SAFETY DATA SHEET

Page 4 of 7

## SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION CON'T.

**RESPIRATORY PROTECTION:** NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

**PROTECTIVE GLOVES:** NITRILE RUBBER

**EYE PROTECTION:** SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

**OTHER PROTECTIVE EQUIPMENT:** LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT:** 302°C (572°F)

**SPECIFIC GRAVITY:** 1.8-1.9

**VAPOR PRESSURE:** ND

**MELTING POINT:** 0°C (32°F)

**VAPOR DENSITY:** ND  
(AIR = 1)

**EVAPORATION RATE:** ND  
(BUTYL ACETATE = 1)

**SOLUBILITY IN WATER:** <1%

**pH:** NE (ALKALINE)

**COEFFICIENT of WATER/OIL DISTRIBUTION:** ND

**ODOR THRESHOLD:** ND

**APPEARANCE AND ODOR:** PIGMENTED PASTE. AMMONIACAL ODOR.

**% VOLATILES BY VOLUME:** 0%

**% SOLIDS BY WEIGHT:** 100%

## SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** STABLE

**CONDITIONS TO AVOID:** AVOID ELEVATED TEMPERATURES

**INCOMPATIBILITY (MATERIAL TO AVOID):** OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** NONE KNOWN

**HAZARDOUS POLYMERIZATION (REACTIVITY):** WILL NOT OCCUR

## SECTION 11: TOXICOLOGICAL INFORMATION

**LIKELY ROUTES OF EPOSURE:** EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

### EYES:

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

### SKIN CONTACT:

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

### SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

# SAFETY DATA SHEET

Page 5 of 7

## SECTION 11: TOXICOLOGICAL INFORMATION CON'T.

### INHALATION:

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.  
CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

### INGESTION:

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT  
CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

**ACUTE TOXICITY:** NO DATA ON THE PRODUCT ITSELF

#### ACUTE ORAL TOXICITY- COMPONENTS

ASPARTIC ESTER	LD50: >5000 mg/kg	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	LD50: >2000 mg/kg	SPECIES: RAT

#### ACUTE DERMAL TOXICITY- COMPONENTS

ASPARTIC ESTER	LD50: >2000 mg/kg	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	LD50: >2000 mg/kg	SPECIES: RAT

#### ACUTE INHALATION TOXICITY- COMPONENTS

ASPARTIC ESTER	LC50(4 HR): 4.224 mg/l	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	ND	

### SKIN CORROSION/IRRITATION

SLIGHTLY TO MODERATELY IRRITATING

### SERIOUS EYE DAMAGE/EYE IRRITATION

SLIGHTLY TO MODERATELY IRRITATING

### SENSITIZATION

DERMAL: POSITIVE (GUINEA PIG, MAGNUSSON/KLINGMAN (MAXIMIZATION TEST))

### SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

CATEGORY 3 (IRRITATING TO RESPIRATORY SYSTEM)

### SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

ND

**CARCINOGENIC DATA:** NTP: NONE

OSHA: NONE

IARC: YES, 2B

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

## SECTION 12: ECOLOGICAL INFORMATION

### TOXICITY

**AQUATIC TOXICITY:** NO DATA ON THE PRODUCT ITSELF

#### ACUTE TOXICITY TO FISH- COMPONENTS

ASPARTIC ESTER	LC50 (96 HRS): 66 mg/l	SPECIES: ZEBRAFISH
MODIFIED CARBONATE BIS-OXAZOLIDINE	LC50 (96 HRS): 9.22 mg/l	SPECIES: FATHEAD MINNOW

#### ACUTE TOXICITY TO AQUATIC INVERTEBRATES: COMPONENTS

ASPARTIC ESTER	EC50 (24 HRS): 88.6 mg/l	SPECIES: DAPHNIA MAGNA
MODIFIED CARBONATE BIS-OXAZOLIDINE	EC50 (48 HRS): 6.14 mg/l	SPECIES: DAPHNIA MAGNA

## SECTION 12: ECOLOGICAL INFORMATION CON'T.

# SAFETY DATA SHEET

Page 6 of 7

## ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: COMPONENTS

ASPARTIC ESTER EC50 (72 HRS): 113 mg/l SPECIES: FRESH WATER ALGAE  
MODIFIED CARBONATE BIS-OXAZOLIDINE ND

## TOXICITY TO BACTERIA: COMPONENTS

ASPARTIC ESTER ND  
MODIFIED CARBONATE BIS-OXAZOLIDINE ND

## CHRONIC AQUATIC TOXICITY

### CHRONIC TOXICITY TO AQUATIC INVERTEBRATES

LONG LASTING ADVERSE EFFECTS TO AQUATIC ORGANISMS

## PERSISTANCE AND DEGRADABILITY

**BIODEGRADABILITY:** NOT READILY BIODEGRADABLE (BY OECD CRITERIA)

## BIOACCUMULATIVE POTENTIAL

**BIOACCUMULATION:** ND

**MOBILITY IN SOIL:** ND

## SECTION 13: DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHODS:** INCINERATION IS PREFERRED. THIS PRODUCT SHOULD NOT BE ALLOWED TO ENTER DRAINS, WATER COURSES OR THE SOIL. PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

## SECTION 14: TRANSPORT INFORMATION

**DOT PROPER SHIPPING NAME:** NOT REGULATED

**HAZARD CLASS:** NA

**UN NUMBER:** NA

**PACKAGING GROUP:** NA

**DOT PRODUCT RQ LBS (KGS):** NA

**HAZARD LABEL:** NA

**HAZARD PLACARD:** NA

**ADDITIONAL INFORMATION:** NONE

## SECTION 15: REGULATORY INFORMATION

**VOC: COMPONENT:** 0 grams/Liter **AS APPLIED:** < 99 grams/Liter (PART OF MULTI-COMPONENT SYSTEM)

**TSCA (TOXIC SUBSTANCE CONTROL ACT):** ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT):** ND

### SARA TITLE III

**SECTION 312 HAZARD CLASS:** IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD

**SECTION 313 LISTED INGREDIENTS:** NONE ABOVE de Minimus LEVELS

**CALIFORNIA PROPOSITION 65:** THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: CAS # 013463-67-7, CAS # 001333-86-4

# SAFETY DATA SHEET

Page 7 of 7

## SECTION 16: OTHER INFORMATION

INITIAL ISSUE DATE: JUNE 24, 2015

REVISION DATE:

PREPARED BY: J.W. ESSIG

### HAZARD RATING

HMIS:                                      HEALTH    3                                      FLAMMABILITY    1                                      REACTIVITY    0

### LEGEND

ACGIH:                                      AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

OSHA:                                        OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

STEL:                                        SHORT TERM EXPOSURE LIMIT

TWA:                                        TIME WEIGHTED AVERAGE

PEL:                                        PERMISSIBLE EXPOSURE LIMIT

TLV:                                        THRESHOLD LIMIT VALUE

NA:                                        NOT APPLICABLE

NE:                                        NOT ESTABLISHED

ND:                                        NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.