

## SAFETY DATA SHEET

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

#### MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING  
7731 N. 68<sup>TH</sup> AVE.  
GLENDALE, AZ 85303

TRADE NAME: SK-E300 FLEX PASTE PART A  
COLOR: CLEAR  
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### GLOBALLY HARMONIZED SYSTEM (GHS)

CLASSIFICATION: HAZARDOUS  
SKIN IRRITATION: CATEGORY 2  
EYE IRRITATION: CATEGORY 2A  
SKIN SENSITIZATION: SUB-CATEGORY 1B  
GERM CELL MUTAGENICITY: CATEGORY 2  
ACUTE AQUATIC TOXICITY: CATEGORY 2  
CHRONIC AQUATIC TOXICITY: CATEGORY 2

#### GHS LABEL ELEMENTS HAZARD PICTOGRAMS



SIGNAL WORD: WARNING!

#### HAZARD STATEMENTS

H315: CAUSES SKIN IRRITATION  
H317: MAY CAUSE ALLERGIC SKIN REACTION  
H319: CAUSES SERIOUS EYE IRRITATION  
H341: SUSPECTED OF CAUSING GENETIC DEFECTS  
H411: TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

#### PRECAUTIONARY STATEMENTS:

##### PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY  
P264: WASH SKIN THOROUGHLY AFTER HANDLING  
P270: DO NO EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT  
P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE  
P273: AVOID RELEASE TO ENVIRONMENT  
P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

# SAFETY DATA SHEET

Page 2 of 6

## SECTION 2: HAZARDS IDENTIFICATION CON'T.

### RESPONSE

P302+P352: **IF ON SKIN:** WASH WITH PLENTY OF SOAP AND WATER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P333+P313: IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION

P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

### DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

### OTHER HAZARDS

NO DATA AVAILABLE

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| <u>HAZARDOUS INGREDIENTS</u>                     | <u>Wt. %</u> | <u>CAS Number</u> |
|--|--------------|-------------------|
| 4,4'-ISOPROPYLDIPHENOL-EPICHLOROHYDRIN COPOLYMER | 60-100       | 025068-38-6       |
| POLYMER OF EPICHLOROHYDRIN-POLYGLYCOL            | 15-40        | 026142-30-3       |
| NONYLPHENOL                                      | 7-15         | 025154-52-3       |
| SILICON DIOXIDE (AMORPHOUS)                      | 1-5          | 112945-52-5       |

## SECTION 4: FIRST AID MEASURES

**GENERAL:** REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

**EYES:** FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

**SKIN:** REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

**INHALATION:** MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

**INGESTION:** GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

## SECTION 5: FIRE FIGHTING MEASURES

**FLASH POINT:** 93°C (199°F) TCC

**CONDITIONS OF FLAMMABILITY:** NA

**FLAMMABLE LIMITS:** LEL: ND UEL: ND

**OSHA CLASS:** NOT REGULATED

**AUTO IGNITION TEMP:** ND

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>, ALDEHYDES, ACIDS

**SENSITIVITY TO IMPACT:** ND

**SENSITIVITY TO STATIC DISCHARGE:** ND

**EXTINGUISHING MEDIA:** IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

**SPECIAL FIRE FIGHTING PROCEDURES:** WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. WATER SPRAY IS USEFUL IN COOLING FIRE-EXPOSED VESSELS AND IN DISPERSING VAPORS.

# SAFETY DATA SHEET

Page 3 of 6

## SECTION 5: FIRE FIGHTING MEASURES

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

## SECTION 7: HANDLING AND STORAGE

**GENERAL:** STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT.

**STORAGE:** AVOID TEMPERATURE EXTREMES. STORE AWAY FROM EXCESSIVE HEAT, FROM SOURCES OF IGNITION AND FROM REACTIVE MATERIALS.

## SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

### EXPOSURE LIMITS (ppm)

| INGREDIENTS (CAS) | OSHA |      | ACGIH |      | OTHER |
|-------------------|------|------|-------|------|-------|
|                   | TWA  | STEL | TWA   | STEL |       |
| 025068-38-6       | NE   | NE   | NE    | NE   |       |
| 026142-30-3       | NE   | NE   | NE    | NE   |       |
| 025154-52-3       | NE   | NE   | NE    | NE   |       |
| 112945-52-5       | NE   | NE   | NE    | NE   |       |

**LEGEND:** (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK  
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

**ENGINEERING CONTROLS:** NO SPECIFIC CONTROLS NEEDED. GENERAL EXHAUST RECOMMENDED.

**RESPIRATORY PROTECTION:** NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

**PROTECTIVE GLOVES:** NITRILE RUBBER

**EYE PROTECTION:** SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

**OTHER PROTECTIVE EQUIPMENT:** LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT:** >120°C (199°F)

**SPECIFIC GRAVITY:** 1.1-1.2

**VAPOR PRESSURE:** < 0.13 kPa @ 20°C (68°F)

**MELTING POINT:** ND

**VAPOR DENSITY:** ND  
(AIR = 1)

**EVAPORATION RATE:** <1  
(BUTYL ACETATE = 1)

**SOLUBILITY IN WATER:** INSOLUBLE

**pH:** NA

**COEFFICIENT of WATER/OIL DISTRIBUTION:** ND

**ODOR THRESHOLD:** ND

**APPEARANCE AND ODOR:** HAZY STRAW COLORED LIQUID, MILD ODOR

**% VOLATILES BY VOLUME:** 0%

**% SOLIDS BY WEIGHT:** 100%

# SAFETY DATA SHEET

Page 4 of 6

## SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** STABLE;

**CONDITIONS TO AVOID:** NOT APPLICABLE (MATERIAL IS STABLE)

**INCOMPATIBILITY (MATERIAL TO AVOID):** OXIDIZING AGENTS (PERCHLORATES, NITRATES), STRONG ACIDS, HYPOCHLORITES, PEROXIDES.

**HAZARDOUS DECOMPOSITION PRODUCTS:** CO, CO<sub>2</sub>

**HAZARDOUS POLYMERIZATION (REACTIVITY):** WILL NOT OCCUR.

## SECTION 11: TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

#### ACUTE ORAL TOXICITY

VERY LOW TOXICITY IF SWALLOWED. HARMFUL EFFECTS NOT ANTICIPATED FROM SWALLOWING SMALL AMOUNTS

LD50, RAT >15,000 mg/kg

#### ACUTE DERMAL TOXICITY

PROLONGED SKIN CONTACT IS UNLIKELY TO RESULT IN ABSORPTION OF HARMFUL AMOUNTS

LD50, RABBIT 23,000 mg/kg

#### ACUTE INHALATION TOXICITY

AT ROOM TEMPERATURE, EXPOSURE TO VAPOR IS MINIMAL DUE TO LOW VOLATILITY. VAPOR FROM HEATED MATERIAL, MIST OR AEROSOLS MAY CAUSE RESPIRATORY IRRITATION.

LC50 HAS NOT BEEN DETERMINED

### SKIN CORROSION/IRRITATION

PROLONGED CONTACT MAY CAUSE SKIN IRRITATION WITH LOCAL REDNESS

REPEATED CONTACT MAY CAUSE SKIN IRRITATION WITH LOCAL REDNESS

### SERIOUS EYE DAMAGE/EYE IRRITATION

MAY CAUSE EYE IRRITATION

CORNEAL INJURY IS UNLIKELY

### SENSITIZATION

FOR SIMILAR MATERIAL(S):

HAS CAUSED ALLERGIC SKIN REACTIONS IN HUMANS

HAS DEMONSTRATED THE POTENTIAL FOR CONTACT ALLERGY IN MICE

FOR RESPIRATORY SENSITIZATION:

NO RELEVANT DATA FOUND

### SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

EVALUATION OF AVAILABLE DATA SUGGESTS THIS MATERIAL IS NOT AN STOT-SE TOXICANT

### SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

EXCEPT FOR SKIN SENSITIZATION REPEATED EXPOSURES TO LOW MOLECULAR WEIGHT EPOXY RESINS OF THIS TYPE ARE NOT ANTICIPATED TO CAUSE ANY SIGNIFICANT ADVERSE EFFECTS.

**CARCINOGENIC DATA:** NTP: NONE

TERATOGENICITY: NO

EMBRYOTOXICITY: NO

**OSHA:** NONE

**IARC:** NONE

MUTAGENICITY: YES

SYNERGISTIC MATERIAL: NO

## SAFETY DATA SHEET

Page 5 of 6

### SECTION 12: ECOLOGICAL INFORMATION

#### TOXICITY

##### ACUTE TOXICITY TO FISH

MATERIAL IS MODERATELY TOXIC TO AQUATIC ORGANISMS ON AN ACUTE BASIS (LC50/EC50 BETWEEN 1 AND 10 mg/l IN THE MOST SENSITIVE SPECIES TESTED)

LC50, ONCORHYNCHUS MYKISS (RAINBOW TROUT), SEMI-STATIC TEST. 96 HR, 2 mg/l

##### ACUTE TOXICITY TO AQUATIC INVERTEBRATES

EC50, DAPHNIA MAGNA (WATER FLEA), STATIC TEST, 48 HR, 1.8 mg/l

##### ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS

ErC50, SCENEDESMUS CAPRICORNUTUM (FRESH WATER ALGAE), STATIC TEST, 72 HR, GROWTH RATE INHIBITION 11mg/L

##### TOXICITY TO BACTERIA

IC50, BACTERIA, 18 HR, RESPIRATION RATES > 42.6 mg/l

##### CHRONIC AQUATIC TOXICITY

##### CHRONIC TOXICITY TO AQUATIC INVERTEBRATES

MATC (MAXIMUM ACCEPTABLE TOXICANT LEVEL), DAPHNIA MAGNA, SEMI STATIC TEST, 21 d, NUMBER OF OFFSPRING, 0.55 mg/l

#### PERSISTANCE AND DEGRADABILITY

**BIODEGRADABILITY:** BASED ON STRINGENT OECD TEST GUIDELINES, THIS MATERIAL CANNOT BE CONSIDERED READILY BIODEGRADABLE; HOWEVER, THESE RESULTS DO NOT NECESSARILY MEAN THAT THE MATERIAL IS NOT BIODEGRADABLE UNDER ENVIRONMENTAL CONDITIONS.

10 DAY WINDOW: NA

**BIODEGRADATION:** 12%

**EXPOSURE TIME:** 28 DAYS

**METHOD:** OECD TEST GUIDELINE 302B OR EQUIVALENT

**THEORETICAL OXYGEN DEMAND:** 2.35 mg/mg ESTIMATED

#### PHOTODEGRADATION

**TEST TYPE: HALF-LIFE** (INDIRECT PHOTOLYSIS)

**SENSITIZER:** OH RADICALS

**ATMOSPHERIC HALF-LIFE:** 1.92 HR ESTIMATED

#### BIOACCUMULATIVE POTENTIAL

**BIOACCUMULATION:** BIOCONCENTRATION POTENTIAL IS MODERATE (BCF BETWEEN 100 AND 3000 OR LOG POW BETWEEN 3 AND 5)

**PARTITION COEFFICIENT: N-OCTANOL/WATER (LOG P<sub>ow</sub>):** 3.242 @25°C ESTIMATED

#### MOBILITY IN SOIL

POTENTIAL FOR MOBILITY IN SOIL IS LOW (K<sub>oc</sub> BETWEEN 500 AND 2000)

GIVEN ITS VERY LOW HENRY'S CONSTANT, VOLATIZATION FROM NATURAL BODIES OF WATER OR MOIST SOIL IS NOT EXPECTED TO BE AN IMPORTANT FATE PROCESS

**PARTITION COEFFICIENT (K<sub>oc</sub>):** 1800-4400 ESTIMATED

### SECTION 13: DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL METHODS: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.** NOT A HAZARDOUS WASTE BY RCRA CRITERIA (40 CFR 261). PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

**SAFETY DATA SHEET**

**SECTION 14: TRANSPORT INFORMATION**

**DOT PROPER SHIPPING NAME:** RESIN COMPOUND, NOT REGULATED      **HAZARD CLASS:** NA  
**UN NUMBER:** NA      **PACKAGING GROUP:** NA  
**DOT PRODUCT RQ LBS (KGS):** NA      **HAZARD LABEL:** NA  
**HAZARD PLACARD** NA  
**IMO SHIPPING DATA:** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (EPOXY RESIN) , 9, PGIII  
**ICAO/IATA SHIPPING DATA:** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (EPOXY RESIN) , 9, PGIII  
**ADDITIONAL INFORMATION:** NONE

**SECTION 15: REGULATORY INFORMATION**

**VOC: COMPONENT:** 0 grams/Liter      **AS APPLIED:** 0 grams/Liter (PART OF MULTI-COMPONENT SYSTEM)  
**TSCA (TOXIC SUBSTANCE CONTROL ACT):** ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.  
**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT):** ND  
**SARA TITLE III**  
    **SECTION 312 HAZARD CLASS:** IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD  
    **SECTION 313 LISTED INGREDIENTS:** PHENOL  
**CALIFORNIA PROPOSITION 65:** THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE.

**SECTION 16: OTHER INFORMATION**

**INITIAL ISSUE DATE:** MAY 11, 2015      **REVISION DATE:**      **PREPARED BY:** J.W. ESSIG

**HAZARD RATING**

**HMIS:**                                      **HEALTH**    **2**                      **FLAMMABILITY**    **1**                      **REACTIVITY**    **1**

**LEGEND**

**ACGIH:**                      AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS  
**OSHA:**                      OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION  
**STEL:**                      SHORT TERM EXPOSURE LIMIT  
**TWA:**                      TIME WEIGHTED AVERAGE  
**PEL:**                      PERMISSIBLE EXPOSURE LIMIT  
**TLV:**                      THRESHOLD LIMIT VALUE  
**NA:**                      NOT APPLICABLE  
**NE:**                      NOT ESTABLISHED  
**ND:**                      NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.