



The Concrete Overlay Experts™

SAFETY DATA SHEET

Page 1 of 5

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING
7731 N. 68TH AVE.
GLENDALE, AZ 85303

TRADE NAME: SK-P501 PART A
COLOR: CLEAR
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

GLOBALLY HARMONIZED SYSTEM (GHS)

CLASSIFICATION: NOT CLASSIFIED AS HAZARDOUS

GHS LABEL ELEMENTS: NOT APPLICABLE

SIGNAL WORD: NONE

HAZARD STATEMENTS: NONE

PRECAUTIONARY STATEMENTS: NONE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

Wt. %

CAS Number

NONE

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE AFFECTED PERSON FROM AREA. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. IF BREATHING REMAINS OR BECOMES LABORED, SEEK MEDICAL ATTENTION.

INGESTION: GIVE 3 – 4 GLASSES OF MILK OR WATER. **DO NOT INDUCE VOMITING.** SEEK MEDICAL ATTENTION.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: NA

OSHA CLASS: NONE SHOWN

CONDITIONS OF FLAMMABILITY: NA

AUTO IGNITION TEMP.: NA

FLAMMABLE LIMITS: LEL: NE UEL: NE

SENSITIVITY TO IMPACT: NONE

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂,

SENSITIVITY TO STATIC DISCHARGE: NONE

EXTINGUISHING MEDIA: WATER, CO₂, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: POLYMER FILM CAN BURN, MATERIAL CAN SPLATTER ABOVE 100°C

SAFETY DATA SHEET

Page 2 of 5

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT.

STORAGE: STORE BETWEEN 40°F AND 100°F PROTECTED FROM FROST AND DIRECT SUNLIGHT.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS (ppm)

NONE

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >100°C (>212° F)

SPECIFIC GRAVITY: 1.0-1.1

VAPOR PRESSURE: ND

MELTING POINT: ND

VAPOR DENSITY: >1
(AIR = 1)

EVAPORATION RATE: <1
(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: DILUTABLE

pH: 8.0 TO 11.5

COEFFICIENT of WATER/OIL DISTRIBUTION: ND

ODOR THRESHOLD: ND

APPEARANCE AND ODOR: MILKY WHITE LIQUID, MILD ODOR

% VOLATILES BY VOLUME: 68%

%SOLIDS BY WEIGHT: 34%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID ELEVATED TEMPERATURES

INCOMPATIBILITY (MATERIAL TO AVOID): NONE KNOWN

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR

CONDITIONS TO AVOID: KEEP FROM FREEZING

SAFETY DATA SHEET

Page 3 of 5

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

EYES:

ACUTE – MAY CAUSE MILD IRRITATION WITH BLURRED VISION.

CHRONIC– ND

SKIN CONTACT:

ACUTE – TRANSIENT IRRITATION AND REDNESS.

CHRONIC – ND

SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

INHALATION:

ACUTE – INHALATION OF MISTS MAY CAUSE MILD RESPIRATORY TRACT IRRITATION.

CHRONIC – EXCESSIVE EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION OF EYES, NOSE AND THROAT.

INGESTION:

ACUTE – MAY CAUSE MILD IRRITATION OF GASTRO-INTESTINAL TRACT

CHRONIC – ND

CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN.

OVEREXPOSURE EFFECTS: IRRITATION

IRRITANCY: YES - REVERSIBLE

SENSITIZER: NO

ACUTE TOXICITY

ACUTE ORAL TOXICITY

LD50, RAT >5,000 mg/kg

SKIN CORROSION/IRRITATION

RABBIT, NON-IRRITANT

SERIOUS EYE DAMAGE/EYE IRRITATION

RABBIT, SLIGHT IRRITATION

CARCINOGENIC DATA: NTP: NONE

OSHA: NONE

IARC: NONE

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

ACUTE TOXICITY TO FISH

LC50(96 HR): >100mg/l, DANIO RERIO (ZEBRA FISH)

ACUTE TOXICITY TO AQUATIC INVERTEBRATES

EC50(48 HR): 70.7 mg/l, DAPHNIA MAGNA (WATER FLEA),

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS

ND

TOXICITY TO BACTERIA

EC50: > 10,000mg/l

ACTIVATED SLUDGE

SAFETY DATA SHEET

Page 4 of 5

SECTION 12: ECOLOGICAL INFORMATION CON'T.

PERSISTANCE AND DEGRADABILITY

BIODEGARADABILITY: NOT READILY BIODEGRADABLE

BIODEGRADATION: 60%

EXPOSURE TIME: 28 DAYS

METHOD: OECD TEST GUIDLINE 302B OR EQUIVALENT

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: NOT A HAZARDOUS WASTE BY RCRA CRITERIA (40 CFR 261). PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: NOT REGULATED

HAZARD CLASS: NA

UN NUMBER: NA

PACKAGING GROUP: NA

DOT PRODUCT RQ LBS (KGS): NA

HAZARD LABEL: NA

HAZARD PLACARD NA

ADDITIONAL INFORMATION: NONE

SECTION 15: REGULATORY INFORMATION

VOC: COMPONENT = 2 gms/Liter **AS APPLIED** (Part of a multi-component system) = 35 gms/Liter

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): ND

SARA TITLE III

SECTION 312 HAZARD CLASS: SLIGHT HEALTH HAZARD

SECTION 313 LISTED INGREDIENTS: NONE ABOVE de Minimus LEVELS

CALIFORNIA PROPOSITION 65: THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE

SAFETY DATA SHEET

Page 5 of 5

SECTION 16: OTHER INFORMATION

INITIAL ISSUE DATE: JUNE 18, 2015

REVISION DATE:

PREPARED BY: J.W. ESSIG

HAZARD RATING

HMIS: HEALTH 1 FLAMMABILITY 0 REACTIVITY 0

LEGEND

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

STEL: SHORT TERM EXPOSURE LIMIT

TWA: TIME WEIGHTED AVERAGE

PEL: PERMISSIBLE EXPOSURE LIMIT

TLV: THRESHOLD LIMIT VALUE

NA: NOT APPLICABLE

NE: NOT ESTABLISHED

ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.