

Tough-Seal WB 501 Sealer System

SYSTEM DATASHEET

SYSTEM DESCRIPTION

The Tough-Seal WB 501 Sealer System is designed for use over interior conventional and architectural concrete surfaces. This system consists of a fast-curing, two-component water-based epoxy primer and a finish coat of a high-performance, two-component water-based polyurethane coating. It is an excellent choice when a low odor, high-performance sealer system is required. With respects to chemical and abrasion resistance, it is equal to or superior to other commercial solvent-based systems on the market today. Tough-Seal WB 501 will produce only a slight darkening of the substrate to which it is applied, making it ideal for applications where the traditional "color pop or wet look" of a solvent system is not desired. Due to its high level of chemical resistance, it is ideal for automotive areas. Additionally, it has tire stain resistance equal to conventional solvent-based polyurethane systems.

FEATURES & BENEFITS

- Chemical resistant
- Abrasion resistant
- Impact resistant
- Exceptional durability
- Low VOC formulation
- Qualifies for LEED projects
- Available in a satin finish

PRODUCTS

- SK-E200
- SK-P501

SYSTEM USES

Tough-Seal WB 501 Sealer System is designed for interior, conventional and architectural concrete.

COLORS

Tough-Seal WB 501 Sealer System is available in Clear with gloss or satin finish.

PHYSICAL PROPERTIES

| | |
|--|--------------------------------------|
| Gloss (60 degrees) | 90 |
| Gloss (Satin material, 60 degrees) | 50-60 |
| Pendulum hardness, sec ASTM D 4336 | 175 |
| Flexibility ASTM D 222 | Passes 1/8 inch |
| Impact resistance ASTM D 2794 | Passes 3/8 inch-pounds direct impact |
| Tabor abrasion (1000 gm. Load, 1000 cycles, CS 17 Wheel) | 32 mg. loss |
| Adhesion to concrete ASTM D 451 | Concrete fails before loss of bond |
| Volatile Organic Compounds | 100 grams/liter |

SURFACE PREPARATION

Surface must be clean, dry and profiled prior to installation. Acceptable methods for preparation are diamond grinding or acid etching. If acid etching, follow APF written instructions. Concrete must have a minimum surface profile ICRI CSP 1, or a texture similar to 150-grit sandpaper.

CHEMICAL RESISTANCE

Please refer to the Arizona Polymer Flooring Chemical Resistance Guide for fully system chemical resistance.

INSTALLATION

Please refer to the *Tough-Seal WB 501 Sealer System Application Instructions* for information on installing this system.

Super-Krete Products is a Division of Arizona Polymer Flooring, Inc.

© 2016 Arizona Polymer Flooring, Inc.

4565 W Watkins St. / Phoenix, AZ 85043

800.562.4921 / 623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com



Tough-Seal WB 501 Sealer System

SYSTEM DATASHEET

MOISTURE VAPOR EMISSIONS PRECAUTIONS:

All concrete floors not poured over an effective moisture vapor retarder are subject to possible moisture vapor transmission that may lead to blistering and failure of the coating system. It is the coating applicator's responsibility to conduct calcium chloride testing in compliance with ASTM F1869, or relative humidity probe testing in compliance with ASTM-F2170, to determine if excessive levels of vapor emissions are present before applying any coatings. Arizona Polymer Flooring offers **S-1300 Pene-Krete®** for cementitious overlay products and **VaporSolve® Moisture Remediation** systems for resinous floor coatings. Consult our technical service department. Arizona Polymer Flooring and its sales agents will not be responsible for coating failures due to undetected moisture vapor emissions.

WARRANTY:

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for damages caused by application of its products over concrete with excessive moisture vapor transmission or alkalinity. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.

Super-Krete Products is a Division of Arizona Polymer Flooring, Inc.

© 2016 Arizona Polymer Flooring, Inc.

4565 W Watkins St. / Phoenix, AZ 85043

800.562.4921 / 623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com

